

# 250 CFM 12-VOLT DC AFTERCOOLER



A moisture management system removes moisture, oil, and other debris from the abrasive blasting air stream. Moisture and debris in an abrasive blasting system will cause abrasive to clump, clogging the metering valve, hoses, and nozzle. Dry, clean compressed air prevents clumping, increases production and reduces maintenance costs. The Marco<sup>®</sup> 250 CFM 12-Volt DC Aftercooler removes up to 95% of moisture, oil, and other debris commonly found in compressed air. Dry air eliminates wet abrasive, typically clogging metering valves and leading to excessive wear, resulting in costly downtime and additional maintenance. Commonly used with abrasive blasting pots, airless sprayers, conventional sprayers, and pneumatic tools. Typical applications include blast yards, bridges, oil refineries, pipelines, shipyards, and storage tanks.



## APPLICATION VERSATILITY

The Marco 250 CFM 12-Volt DC Aftercooler has a compact design for setting up anywhere on the work site.

## REDUCED DOWNTIME

Dry air is a critical component of any air-blasting application. Wet abrasive clogs abrasive metering valves and leads to excessive wear, resulting in costly downtime and additional maintenance.

## COMMITMENT TO QUALITY

Our commitment to producing the highest quality products in the industry demands strict control over our raw materials and manufacturing processes. All components used in the manufacturing of Marco products adhere to strict process controls as specified by Allredi's Quality and Engineering team.



The 16" electric fan moves air over the aluminum core to accelerate cooling.



The aftercooler core is protected by a heavy-duty mesh grating.



The Marco 250 CFM 12-Volt DC Aftercooler includes a sturdy handle for ease of transport and a bracket for storing the 25 feet of 12-gauge electrical cord.



The large footprint of the Marco 250 CFM 12-Volt DC Aftercooler provides a stable base to reduce tipping.



800.252.7848



SALES@ALLREDI-US.COM



WWW.ALLREDI-US.COM



## KEY FEATURES:

- 16" 12-Volt DC electric fan
- 25 ft. of 12-gauge electrical cord with battery clamps
- 2" inlet and outlet ports
- Aluminum aftercooler core

## Empty Weight:

85 pounds

## Dimensions:

Overall Height: 26"

Width: 26"

Depth: 18"

## OPTIONAL ACCESSORIES

### Air Hose Fittings & Ball Valves




Air hose fittings are available in 2 lug, 4 lug and hammer lock styles. ball valves are available in 1/4" I.D. – 4" I.D.

### Coupled Air Hose



Additional air hose, air hose couplings, and air hose assemblies are available.

### Whip Check Safety Cables



A Whip Check at each hose connection can prevent serious injury due to hose or coupling failure and meets OSHA requirements. (29 CFR 1926.302)

### Marco® Moisture Separators



Marco® Moisture Separators will remove condensed moisture from the air stream.



800.252.7848



SALES@ALLREDI-US.COM



WWW.ALLREDI-US.COM