

MARCO® 250 CFM CART MOUNTED AFTERCOOLER



The 250 CFM Cart Mounted Aftercooler removes up to 95% of moisture, oil, and other debris commonly found in compressed air. Dry air is a critical component of any blast system. Wet abrasive clogs abrasive metering valves and leads to excessive wear, resulting in costly downtime and additional maintenance. The 250 CFM Cart Mounted Aftercooler is commonly used with blast pots, airless spray equipment, conventional spray equipment, and pneumatic tools. Typical applications for the 250 CFM Cart Mounted Aftercooler include: blast yards, oil refineries, pipelines, storage tanks, shipyards, and bridges.



APPLICATION VERSATILITY

The cart mounted design provides mobility on the jobsite.

REDUCED DOWNTIME


Dry air is a critical component of any blast application. Wet abrasive clogs abrasive metering valves and leads to excessive wear, resulting in costly downtime and additional maintenance.

COMMITMENT TO QUALITY


Our commitment to producing the highest quality products in the industry demands strict control over our raw materials and manufacturing processes. All components used in the manufacturing of Marco products adhere to strict process controls as specified by Allredi's Quality and Engineering team.



Electric models include a starter wiring box as a standard feature.



Pneumatic models include an easily accessible pressure regulator, particulate and moisture filter, and lubricator, which can be adjusted to regulate the volume of air and oil supplied to the fan for optimal performance.



The Extractor Junior Moisture Separator traps condensed moisture and debris before it can enter the aftercooler, greatly increasing the effectiveness of the aftercooler.



800.252.7848



SALES@ALLREDI-US.COM



WWW.ALLREDI-US.COM

MARCO® 250 CFM CART MOUNTED AFTERCOOLER



Marco
Powered by **ALLREDI**

KEY FEATURES:

Pneumatic or Electric Driven Fans

1-1/4" Outlet Port

Industrial Cart with 16" Wheels

Galvanized Fittings

.....
Empty weight: 300 lbs.

Height: 49"

Width: 43"

Depth: 31"
.....

Power Source:

Pneumatic or Electric in
115-Volt or 230-Volt

OPTIONAL ACCESSORIES



Large Capacity Coalescing Tank

A large capacity coalescing tank will remove condensed moisture from the air stream.



Air Hose Fittings and Ball Valves

Air hose fittings are available in 2 lug, 4 lug and hammer lock styles. ball valves are available in 1/4" I.D. – 4" I.D.



Coupled Air Hose

Additional air hose, air hose couplings, and air hose assemblies are available.



800.252.7848



SALES@ALLREDI-US.COM



WWW.ALLREDI-US.COM

Allredi™ and Marco® are registered trademarks of Allredi, LLC.
All other brand names or marks are used for identification purposes and are trademarks of their respective owners

Literature #105M097_09/26/2022