



ATTRIBUTES:

LINER

13g Green HDPE A4 Basetek Liner

COATING

Black HCT® MicroFoam Nitrile Palm Coating

FEATURES:

- Enhanced Grip in Oily and Greasy Environments

APPLICATIONS:

- Automotive Manufacturing
- Metal Stamping
- Steel Handling
- Construction
- Recycling

Armor Guys reference number : 02-024

CATEGORY:

Basetek

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



SPECIFICATIONS

| | |
|-------------------|---------------------------------|
| LINER MATERIALS | 13g Green HDPE A4 Basetek Liner |
| COATING MATERIALS | Black HCT® MicroFoam Nitrile |
| WRIST DESIGN | Continuous Knit |
| SIZES | XS-XXL |

| PACKAGING | | | | | | |
|------------|--------|------|--------|-------|-------|------|
| CASE SIZE | XS | S | M | L | XL | XXL |
| PER CARTON | 12DZ | 12DZ | 12DZ | 12DZ | 12DZ | 12DZ |
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Blue |
| ORIGIN | PRC | | | | | |

PERFORMANCE LEVEL

| | | | | | | |
|--------------|---------------------------|---|---|---|---|---|
| EN388: 4444D | EN Level 4 Cut Resistance | | | | | |
| ABRASION | 0 | 1 | 2 | 3 | 4 | 5 |
| CUT | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | 5 |
| CUT TDM TEST | A | B | C | D | E | F |