

7016B

Contractor+ 1D Standard Non-belted Full Body Harness

Features :

- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs
- Plated alloy steel low-profile spring tension roller torso adjusters provide simple adjustment.
- Breathable padded air-mesh shoulder yoke delivers added user comfort
- Paired lanyard parking keepers provide balanced function for single and twin-leg personal SRLs
- Plated alloy steel dorsal D-ring with mating buckle chest and tongue buckle leg closures
- Uncommonly outfitted with 9 grommeted leg adjustment positions for a wider range of fit
- Complies with ANSI Z359.11-2014



Material Specifications	
Webbing	Polyester; 5,000 lb min. static strength
D-ring	Plated alloy steel; 5,000 lb min. static strength
Buckles and Adjusters	Plated alloy steel; 3,372 lb min. static strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.11-2014
OSHA	1926.502 and 1910.66
CSA	Z259.10-2018

Sizes & Part Numbers			
7016BXS - XS	7016B - UniFit (S, M, L)	7016BX/2X - Dual-size XL/2X	7016B3X - 3X