

**8253**

**3' ViewPack® Energy Absorbing Lanyard, Single-leg with Steel Snap Hooks**

**Features :**

- Heavy-duty 1" polyester web construction throughout
- 3' length is ideally suited for applications where restricted fall clearances are present.
- Energy absorber features patented ViewPack® cover with inspection window
- ViewPack® cover also features WrapPack label protection
- Includes alloy steel snap hooks for harness attachment and anchorage connection
- Complies with ANSI Z359.13-2013



Material Specifications	
<b>Webbing</b>	Polyester; 5,000 lb min. static strength
<b>Energy Absorber</b>	Polyester tear-away
<b>Connectors</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	5,000 lb min.
<b>ANSI Lanyard Class</b>	6' free fall
<b>Max. Arrest Distance</b>	48"
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.13-2013

