

# 8259Y3

## 6' Internal Energy Absorbing Lanyard, Double-leg with Steel Connectors

**Features :**

- Low-profile design constructed with tubular polyester webbing
- Features full-length internal energy absorber and visual fall indicator.
- Includes alloy steel snap hook for harness attachment and rebar hooks for anchorage connections
- Double-leg design facilitates 100% tie-off
- Rebar hooks feature transverse load rated gates
- Complies with ANSI Z359.13-2013



Material Specifications	
<b>Webbing</b>	Polyester; 5,000 lb min. static strength
<b>Energy Absorber</b>	Polyester POY
<b>Connectors</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	5,000 lb min.
<b>ANSI Lanyard Class</b>	6' free fall
<b>Max. Arrest Distance</b>	48"
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>ANSI</b>	Z359.13-2013
<b>OSHA</b>	1926.502 and 1910.66