

84202DC

Cable Carabiner Sling Anchor with Vinyl Coated Galvanized Steel Cable

Features :

- Hard-wearing 1/4" vinyl coated galvanized steel cable tolerates demanding work environments
- Non-choking, trouble-free wrap-around and connect installation.
- Captivated carabiner and one connecting ring secure anchor to overhead structures
- Secondary connecting ring facilitates connection of SRL or lanyard
- Features plated alloy steel connecting rings and carabiner
- Assembled with steel thimbles and swaged aluminum ferrules
- Vinyl coating adds a layer of protection and provides easier clean-up
- Complies with ANSI Z359.18-2017



Material Specifications	
Cable	1/4" vinyl coated galvanized steel; 5,000 lb min. static strength
D-rings	Plated alloy steel; 5,000 lb min. static strength
Carabiner	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	5,000 lb min.
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 425 lb max.

Compliant With:	
ANSI	Z359.18-2017
OSHA	1926.205 and 1910.66

Sizes & Part Numbers				
84202DC3 - 3'	84202DC4 - 4'	84202DC - 6'	84202DC8 - 8'	