



SPECIFICATION SHEET

COATING Gray Polyurethane

Palm Coating







A3 Basetek Liner **FEATURES:**

13g Salt and Pepper HDPE

ATTRIBUTES:

02-013

LINER

• Positive Grip in Dry and Light Oil Environments

APPLICATIONS:

- · Automotive Manufacturing
- Light Manufacturing
- · Sheet Metal Handling
- Metal Stamping
- Construction

Armor Guys reference number: 02-013

CATEGORY:

Basetek

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)





This product can expose you to N,N-Dimethylformamidewhich is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HDPE A3 Basetek Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XS-XXL

PACKAGING						
CASE SIZE	XS	S	М	L	XL	XXL
PER CARTON	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ
CASE WEIGHT	19.40/lbs	20.28/lbs	21.38/lbs	23.36/lbs	24.25/lbs	26.01/lbs
CUFF COLOR	■ Purple	■Red	Yellow	■Brown	■Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4442C	EN Level 4 Cut Resistance							
ABRASION	0	1	2	3	4	5		
CUT	0	1	2	3	4	5		
TEAR	0	1	2	3	4	5		
PUNCTURE	0	1	2	3	4	5		
CUT TDM TEST	А	В	С	D	Е	F		